

Disan is proud to introduce the new central units of the Matrix range. A combination of technology, simplicity and well-being. The Matrix range is ideal: compact, practical and really powerful. Two different models: The basic model will satisfy the requirements of modern buildings, with small surfaces, but really sensitive to costs. The other fully developed model is for customers with highest expectations, that always demand products with full optional and at the state of the art.















Compact dimension, offering space saving advantages and to be installed in hidden small places, but keeping an elevated air performance and large-capacity of dust container (up to 12 litres)




MATRIX



Silent like any other power unit in its class, thanks to central positioning of motors and internal sound suppression system.







Steady control of operation, hours' counter, state of filters, level of dust container and other extraordinary maintenance alarms.



High efficiency motors, for ultimate air performances with an eye to the energy consumption. Serial thermic sensors, available with soft-start and progressive control of the power.






Dual vacuum air intakes and outtakes for connection from

right or left side. Changeable

in only 3 minutes. Together

with the fast fixing bracket can be fixed to the wall in



Matrix PT Basic version

Primary filtration with hygienic and practical disposable bags with double layer and quick lock. Secondary filtration in expanded polyethylene (HEPA rated).



Model Matrix PT - This version is very simple: with disposable bag filter, motor protection, frontal switch, control board. Quite sober, but very reliable and economic.


Matrix FF Version Plus

Patented filtering system with permanent flat cartridge with self-cleaning. Extractable drawer for easy collection of the dust and debris, without contact with hands.



Model Matrix FF- This version has a more aesthetical appeal and many functions: with a washable flat filter of wide surface, double protection, display FIP, advance functions, soft-start with triac, microprocessor SP, differential pressure switch, etc.

Approximate application:	MATRIX FF		MATRIX PT	
Surface up to	m^2	130	m ²	130
Length of tubing	m	ca. 30	m	ca. 30
Inlet socket max.	Stk.	3-4	Stk.	3-4



Specifications:	MATRIX FF		MATRIX PT	
Motor power	Kw	1,5	Kw	1,5
Turbine stages	Stk	1	Stk	1
Voltage requirement	Volt	230	Volt	230
EC Safety degre		IP45		IP45
Suction power max	mbar	260	mba	r 260
Airflow max	m ³ /h	220	m ³ /h	190
Airwatt Ø32mm	W	378	W	421
Filter	1	flat filter paper b		paper bag
Filter surface	cm ²	5200	cm ²	3350
Housing		ABS		ABS
Dust capacity	L	5	L	11
Dimensions	27>	(39x49,5		27x39x49,5
Sound level	dB	59	dB	59
Weight gross/net	kg	9,5/7,6	kg	9,4/7,5





Disan Srl
Via di Mezzo ai Piani, 13A • I - 39100 BOLZANO
Tel: +39 0471 971000 • Fax: +39 0471 978888
info@disan.com • www.disan.com



